

**SECRET**

20 December 1957

MEMORANDUM FOR: 

TSS/APD

25X1

SUBJECT: Viewer and Light Table Requirements of HTAUTOMAT

1. The following represents a summary of present and anticipated HTAUTOMAT requirements for film viewers and light tables, and special equipment necessary for processing  materials:

25X1

Fixed 2X and 4X 70mm enlarger (a prototype of this item for 4X only is available for study at APEL, Johnsville, Pa.) 3 each.

Bausch and Lomb 6" autofocus rectifier. 1 each.

Light table for simultaneous viewing of three rolls of 70mm film and one roll of standard 9 $\frac{1}{2}$ " film. 3 each.

PSC 70mm dryer and processor (automatic). 2 each.

Nikor developing tanks with reel; loading stand and two extra tanks for 70mm x 100' film. 3 each.

Light tables with 19" x 37" viewing surface for 18" roll film or 2-9 $\frac{1}{2}$ " rolls simultaneously. 10 each.

Light tables (as above) adaptable to a binocular bridge for roll stereo viewing, similar to the B and L roll stereo viewer. 10 each.

Light tables for 9x18 film viewing (standard AF type). 10 each.

Telecordex units. 3 each.

Telereadex unit with 9 $\frac{1}{2}$ " roll film adapter and angle measuring and read-out capability. 1 each.

**SECRET**